## H<sub>2</sub>O-US3

## **Product Overview**

The H<sub>2</sub>O-US3 is a high capacity undersink water filter designed to be installed out of site under the sink and connects to separate long-reach faucet. The filter uses an advanced proprietary replaceable cartridge with granular coconut shell carbon (GAC) and KDF 55 process media to reduce chlorine, organic volatile compounds (VOC) and other contaminants responsible for taste, appearance and odor that may be present in municipally supplied water. Significantly improves taste, odor and appearance of tap water in the kitchen.

## **Product Highlights**

- Replaceable Cartridge System with 25,000 gal capacity
- KDF® / GAC Filter Media
- · 5-stage filtration and purification system
- · Proprietary filtration cartridge
- · Includes easy-installation kit
- · Connects to separate, chromed, long-reach faucet
- · Available inline for direct connection to faucet
- Bacteriostatic media prevents bacteria growth (algae, fungi)

faucet, fittings and adapters

- · Improves taste and color, eliminates odors
- · Reduces most EPA listed contaminants
- · Includes prorated warranty

Max Capacity	25,000 gal (94,635 L)
Recommended Flow	1.0 gpm (3.79 lpm)
Unit Height	17" (43.18 cm) including fitting
Unit Width	4" diameter (10.16 cm)
Unit Box Dimensions	18" x 7" x 6" (45.72 x 17.78 x 15.24 cm)
Unit Shipping Weight	7.5 lbs (3.4 kg)
Packing	6 per master case
Master Dimensions	21" x 18" x 13" (53.34 x 45.72 x 33 cm)
Master Case Weight	45 lbs (20,4 kg)

